

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the the (X) utility,
() design, () plant patent application of:

INVENTOR(S): William T. Freeman / William S. Yerazunis /
Walter A. Hiatt

FOR: VIDEO RECORDING DEVICE RESPONSIVE TO TRIGGERING
EVENT

Enclosed are:

(X) 23 pages of specification (X) Abstract
(X) Oath or Declaration (X) Power of Attorney
(X) 7 sheets of () Formal (X) Informal Drawings.

(X) An assignment of the application
to Mitsubishi Electric Information Technology Center America, Inc.

() Preliminary Amendment () Information Disclosure
() Oath or Declaration Statement
() Associate Power of Attorney () Power of Attorney
() Verified Statement Under 37 CFR 1.9 and 1.27

The filing fee is calculated as follows:

FOR	NUMBER FILED	CLAIMS AS FILED		RATE	AMOUNT
		NUMBER EXTRA		LARGE SMALL	
BASIC FEE					
Utility	xxxxxxx	xxxxxxx	\$770.00	\$385.00	770.00
Design	xxxxxxx	xxxxxxx	\$320.00	\$160.00	
Plant	xxxxxxx	xxxxxxx	\$530.00	\$265.00	
Total Claims	-20	- 11-	x 22.00	x 11.00	242.00
Independent Claims	4 -3	- 1-	x 80.00	x 40.00	80.00
Multiple Dependency			\$260.00	\$130.00	
Late Fee Surcharge			\$130.00	\$ 65.00	
Non-English Language Fee			\$130.00		
Assignment Recording Fee			\$ 40.00	\$ 40.00	40.00
TOTAL FEE					1,132.00

(X) A check in the amount of \$ 1,092.00 to cover the filing
fee is enclosed.

() Please charge Deposit Account No. _____ in the
amount of \$ _____.

(X) A check in the amount of \$ 40.00 to cover the cost
of the Assignment Recording Fee is enclosed.



45080" E6490680

() This application is filed under the provisions of 37 CFR 1.53, and does not include:

() Oath or Declaration

() Filing fee

(X) The Commissioner is hereby authorized to charged payment of the following fees or credit any overpayment to Deposit Account No. 20-0449. A duplicate copy of this sheet is enclosed.

(X) Any additional filing fees required under 37 CFR 1.16

(X) Any patent application processing fees under 37 CFR 1.17

() The Issue Fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b)

() Priority is claimed under 35 USC 119 based on the following:


Serial No.

Date Filed

Country

() Certified copy (copies) enclosed.

Date: 8/5/97


Robert K. Tendler

Reg. No. 24,581

ADDRESS: 65 Atlantic Avenue
Boston, MA 02110

TELEPHONE: 617-723-7268

APPLICATION FOR LETTERS PATENT

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT William T. Freeman, a citizen of the United States of America, having a residence at 16 Half Moon Hill, Acton, Massachusetts 01720; William S. Yerazunis, a citizen of the United States of America, having a residence at 24 Nash Road, Acton, Massachusetts 01720; and Walter A. Hiatt, a citizen of the United States of America, having a residence at 310 College Farm Road, Apt. 3, Waltham, Massachusetts 02154 have invented a certain new and useful VIDEO RECORDING DEVICE RESPONSIVE TO TRIGGERING EVENT.

0805493 080597

VIDEO RECORDING DEVICE RESPONSIVE TO TRIGGERING EVENT

GOVERNMENTAL RIGHTS

Not Applicable

RELATED APPLICATIONS

Not Applicable

BACKGROUND OF THE INVENTION

The present invention relates to video recording devices and more particularly to a video camera which stores successive frames in at least one circular buffer memory and which may continue to store frames for a period following the occurrence of a triggering event.

Numerous applications exist in which it is desirable to retain a video record for evidentiary or historical purposes. For example, in an automobile, or on a bicycle or motorcycle, it would be desirable to record a video image of the circumstances existing immediately prior to an accident after an accident. Additionally, in security applications, it would be highly desirable to be able to record a video image of the circumstances existing immediately prior to an event triggering an alert condition and following the triggering of such a condition. Additionally, in numerous other applications it would be desirable to be able to create a video record of circumstances existing both before and after a triggering event.

A number of image recording devices are well known in the art. In time lapse photography a series of still pictures are taken over a period of time. Such pictures are typically taken with a periodically actuated still or a motion picture camera and employ photographic film. The cameras are loaded with a limited supply of film and the camera must be reloaded when the supply of film is exhausted. Accordingly, such devices are not well suited for applications in which it is desired to record images over a long period of time when only a very short period of time is of interest and the particular period of interest cannot be predicted.

In security applications, a video camera is often employed to record a video image on magnetic tape on a continuous basis. When the tape is exhausted it must be replaced.

Both photographic cameras employing photographic film and video cameras utilizing magnetic tape as the recording media employ mechanical transport mechanisms which are susceptible to failure when subjected to shock and vibration. Accordingly, such devices are ill suited for use in applications and environments in which shock and vibration are the norm.

For the above reasons, a video recording device would be desirable which could record video frames on a continuing basis and capture a video record of circumstances surrounding a triggering event occurring at an unpredictable time. It would further be desirable for such a device to be compact, lightweight, cost effective and avoid the aforementioned deficiencies of prior art

08906493 "080507"

video recording devices employing mechanical transports.

SUMMARY OF THE INVENTION

In accordance with the present invention, a video recording device is disclosed which is contained within a compactly sized housing. One or more video image sensors are mounted to the housing. Alternatively, one or more video image sensors are provided which are electrically coupled to the housing via wires so as to permit the image viewing area to be selected freely via suitable mounting of the sensors by a user. The video recording device records video frames successively in at least one circular buffer memory organized as a continuous loop overwriting the oldest frame within the respective buffer memory with a more recently received frame. Upon receipt of a triggering event, a predetermined number of additional frames are recorded within the circular buffer memory at which point recording ceases. A plurality of circular memory buffer groups may be provided to extend the overall recording time for the device by selectively storing video data samples to the respective buffer groups. The foregoing video recording device can be fabricated as a compact transportable unit which employs no moving parts and which has relatively low power consumption facilitating battery operation in certain embodiments.

More specifically, a video camera is provided which compares a lens and a video image sensor. The lens is employed to focus a video image on a video image sensor such as a charge coupled device sensor or an artificial retina as hereinafter discussed. The output of the video image sensor comprises an analog signal which is coupled to one or more A/D converters. The A/D converter(s) is sampled to generate a digital representation of the video image sensor analog output signal. A predetermined number of digital samples comprise one video frame. The digitized output signal(s) from the A/D converter(s) is coupled to a central controller in the form of a microprocessor or any other suitable controller. The microprocessor compresses the digitized frame data and stores the compressed frame data in the next sequential location of the circular buffer. In one embodiment, the digitized frame data is encrypted prior to storing the same in the buffer so as to prevent unauthorized access to such data. The circular frame buffer comprises a semiconductor memory such as DRAM or any other suitable high speed semiconductor memory.

Upon detection of a trigger event, the video recording device records a predetermined number of additional frames and then ceases to record further frame data. In this manner, a video event record is obtained which commences prior to the triggering event and extends in time after the triggering event. Triggering events may include an accelerometer output signal crossing a predetermined

08906493 080597

threshold, a signal employed to initiate air bag deployment in an automobile, a signal representing a recognized change in a video image or acoustic signal, a signal indicative of a security or fire alarm condition, a button actuated by a user, or any other suitable activation signal known in the art. Further, an activation button is provided which permits a user to take a single frame "snap shot" which is retained within the buffer memory until purged upon user activation of a purge button.

A serial output channel is provided to permit recorded frame data to be downloaded to a computer for viewing.

The above described apparatus thus provides a video recording device which has high reliability, is compact, cost effective and suitable both for consumer and commercial applications.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood by reference to the following Detailed Description of the Invention in conjunction with the drawings of which:

Fig. 1 is a pictorial view illustrating an application for use of the video recording device of the present invention;

Fig. 2a is a pictorial view of a housing for a video recording device in accordance with the present invention in which a camera comprising a lens and image sensor is mounted within the housing;

Fig. 2b is a pictorial view of an alternative embodiment of a housing for the video recording device of Fig. 1 in which the camera is disposed external to the housing and in electrical communication with video processing circuitry (not shown) disposed within the housing;

Fig. 3 is an electrical block diagram of a video recording device in accordance with the present invention;

Fig. 4a is a simplified schematic representation of a circular memory buffer employed within the video recording device of Fig. 3;

Fig. 4b is a representation of a semiconductor memory buffer employed in the video recording device of Fig. 3 to implement a circular memory buffer and associated head and tail pointers;

Fig. 5 is a flowchart illustrating the recording method in accordance with the present invention;

Fig. 6 is a table illustrating one storage technique for storage of video data in the semiconductor memory buffer;

Fig. 7 is a table illustrating an alternative storage technique for storage of video data in the semiconductor memory buffer; and

Fig. 8 is a table illustrating a further alternative storage technique for storage of video data in the semiconductor memory buffer.

08906493 030597

DETAILED DESCRIPTION OF THE INVENTION

An application of a video recording device 2 in accordance with the present invention is illustrated in Fig. 1. The recording device 2 is mounted within a first vehicle 4 which has come to a stop behind a second vehicle 6 at an intersection. Vehicle 6 has also come to a stop at the intersection, however, has backed up so as to impact vehicle 2 causing damage to vehicle 4. It would be highly desirable for the driver of vehicle 4 to have an evidentiary record which establishes that the accident was caused by vehicle 6 since it would normally be presumed in such a circumstance that the driver of vehicle 4 was the cause of the accident. The video recording device 2 in accordance with the present invention generates such a record by continually recording video frames in a circular buffer at a predetermined frame rate. In response to a trigger event, such as an air bag activation signal or a button activated by the driver, the video recording device records a predetermined number of additional frames before ceasing to record further frames. In the foregoing manner, the driver of vehicle 4 can establish the true cause of the accident. The foregoing example is provided solely as an illustration of the operation of the video recording device 2 of the present invention.

A housing 10 for a video recording device 2 in accordance with the present invention is depicted in Fig. 2a. The housing 10 includes a camera comprising a lens 12 and a video image sensor (not shown) which may comprise a charge coupled device (CCD), an artificial retina, or any other suitable optical sensor operative to provide output signals when a video image impinges the sensor. By way of illustration, the sensor may comprise a model TC241 CCD array manufactured by Texas Instruments or an artificial retina such as identified and described volume 372, number 197 NATURE, 1994 which is incorporated herein by reference. The lens 12 is specified to have appropriate optical characteristics and is oriented so as to focus a video image of the desired field of view on the video image sensor. While the housing of Fig. 2a illustrates the use of a single camera, multiple cameras may be employed and selectively oriented to capture images at desired viewing angles. For example, one camera may be positioned at the forward edge 14 of the housing 10 and a second camera at the trailing edge 16 of the housing 10 to capture images at 180° viewing angles. Additionally, by way of example, cameras may be disposed on the leading edge 14 and a side edge 17 of the housing 10 so as to capture video images along orthogonal viewing angles. It is further understood that any desired number of cameras may be employed.

Another embodiment of a video recording device assembly in accordance with the present invention is depicted in Fig. 2b. The video recording device illustrated in Fig. 2b includes a housing 18

08905493 080597

and a camera 20 which is disposed external to the housing 18. The lens 22 focuses a video image on the sensor 24 which, in the preferred embodiment, produces an electrical output signal for communication to a video signal processor. The sensor 24 communicates the electrical output signal via wires 26 to the video signal processor disposed within the housing 18. The wires 26 may be coupled to the circuitry (not shown) via a connector or alternatively may be hardwired to such circuitry. While a single video image sensor 20 is depicted in Fig. 2b, as with respect to Fig. 2a, the video recording device in accordance with the present invention may employ multiple cameras 20 which may be selectively mounted and positioned at desired viewing angles so as to permit a corresponding number of video images to be captured.

The housings illustrated in Figs. 2a and 2b may be fabricated in a PCMCIA configuration with a PCMCIA connector disposed at one end so as to permit the housing to be inserted into a laptop computer or any other suitable computer having a PCMCIA interface to permit viewing of images captured within the video recording device.

A block diagram of the video recording device in accordance with the present invention is depicted in Fig. 3. As illustrated in Fig. 3, the recording device includes a camera 40 and video electronics 42. The camera 40 is comprised of a lens 44 which is disposed a predetermined distance d from the surface of an image sensor 46. The image sensor 46, as described above, may comprise a charge couple device array, an artificial retina, or any other suitable image sensor operative to provide an output signal representative of a video image which impinges upon the sensor. In a preferred embodiment employing a CCD array as the sensor 46, the CCD array produces an analog output signal which is electrically coupled to an analog to digital converter 48 via a signal path 50. The analog to digital converter may comprise a model AD775 A to D converter manufactured by Analog Devices, Inc. or any other suitable analog to digital converter. Support electronics 52 are provided which include a clock generator which is coupled to the analog to digital converter 48 to permit the sensor output 50 to be sampled at predetermined intervals and other conventional timing circuitry. The analog to digital converter 48 generates a digital representation of the sensor output signal 50. A predetermined number of samples of the sensor output signal 50 comprise a single video frame. For example, in one exemplary embodiment, each frame contains 256 horizontal samples by 128 vertical samples yielding an uncompressed size of 32,768 bytes. Sixty four such frames can be stored in a two (2) megabyte memory.

Generally, color images require approximately thirty (30) percent more storage space. One could thus store approximately fifty (50) frames of uncompressed color image information in the

two (2) megabyte memory.

For images of the above identified sizes a compression ratio of four to one (4:1) is readily achievable. Such would permit 256 black and white images or 200 color images to be stored in the two (2) megabyte memory. At a recording rate of ten (10) frames per second, the two (2) megabyte memory will accommodate thus accommodate 25 seconds of black and white images or 20 seconds of color images. A greater recording interval may be achieved by employing a lower sampling rate or by utilizing a larger memory.

The output of the analog to digital converter is electrically coupled to inputs of a central control processor 54 via signal path 56 which comprises a parallel signal bus. The central control processor 54 in a preferred embodiment, may comprise an M32RD microprocessor which is commercially available from Mitsubishi Electric, any other suitable microprocessor, an Application Specific Integrated Circuit (ASIC) or any other suitable implementation of a central control processor operative to perform the presently described functions.

The central control processor 54 is coupled to a semiconductor memory 58 which comprises a DRAM in preferred embodiment. Within the M32RD device referenced above, two (2) megabytes of DRAM is incorporated in the commercially available device. Thus the microprocessor 54 and the DRAM 58 may be obtained as a single integrated circuit. Additional semiconductor memory 60 may be coupled to the microprocessor 54 via a bus 62 in the event that it is desired to increase the semiconductor memory capacity of the video recording device. It may be desired to increase the memory capacity of the recording device to permit a greater number of frames to be captured or to accommodate the storage of video images received from plural cameras.

The central control processor 54 executes a control program which is stored within a Read Only Memory (ROM). The ROM 64 is coupled to the central control processor via bus 66. The central control processor 54 is provided with a number of inputs 68 which permit activation of the video recording device and control of the device by a user. Exemplary inputs comprise, an event sensor 70, a "capture" button 72, a "still" button 74 and a "purge" button 76. Additionally, the central control processor 54 includes a serial output channel 78 which permits stored video images to be downloaded to an external video device for viewing. In one embodiment, the serial output channel is compatible with the well known Xmodem serial protocol. It is appreciated that any suitable serial channel protocol may be employed.

The central control processor 54 receives successive samples of frame data from the analog to digital converter 48 and compresses the received frame data in order to reduce the storage capacity for the captured video data. One image compression

08906493 080597

technique which may be employed is disclosed in U.S. Patent No. 4,917,812 to Adelson and Simoncelli. While any suitable compression technique may be employed, in a preferred embodiment of the invention, an asymmetric compression technique (known in the art) is used which minimizes the computational load on the central control processor to compress the image data during compression of the image data at the expense of greater complexity in the decompression algorithm. The use of an asymmetric compression technique thus places greater processing demands on the processor which will ultimately perform the decompression which, is likely to comprise a personal computer (PC), a workstation, or some other computer which generally possesses the necessary processing speed to perform such decompression or which is not burdened by the constraint of real time processing. In this manner, the video electronics 42 are not burdened with additional cost associated with added processing power.

Following the compression of the frame data, the central control processor stores the compressed data within the semiconductor memory 58. The semiconductor memory 58 is structured as a circular memory buffer as illustrated in Fig. 4a. Thus, following compression, each compressed video frame is stored in the next successive frame buffer location and any frame data continued in such location is overwritten. For example, referring to Fig. 4a, if the last frame were stored at location 3 of the circular buffer 90, the subsequent video frame would be stored at location 4 of the circular frame buffer. The video recording device, absent receipt of some trigger event from the sensor 54 or activation of other input by the user, continues to store captured frame data in successive locations of the circular buffer, overwriting previously received frame data stored in respective buffer locations with the most recently received frame data.

The operation of the circular buffer is described with more particularity below and with respect to Fig. 4b. The semiconductor memory buffer is sized to as to permit the desired number of frames to be concurrently stored in the buffer. The buffer 100 utilizes a plurality of bytes to store each frame as illustrated in frame buffer locations 0 and n. The specific number of bytes required for a particular frame is dependent upon the resolution of the video image sensor 46, the sampling rate of the analog to digital converter 48, and the efficiency of the compression algorithm.

Associated with the semiconductor memory buffer 58 (and additional buffer memory 60 if such is employed) are a tail pointer 102 and a head pointer 104. The head pointer points to the address of the frame buffer location for storage of the next frame data. Such address is offset in the respective frame to address the respective byte for the frame data being stored. For simplicity, the operation of the buffer is explained with respect to the frame

addresses recognizing that plural locations are utilized within the buffer to store the data associated with any given frame.

The head pointer 104 points to the location for storage of the incoming frame data. Thus, if the next frame data is to be stored in location 4, the head pointer is set to location 4. Once all of the data corresponding to frame 4 has been stored in the buffer, in normal operation and in the absence of a trigger event, the head pointer is incremented to point to frame number 5. As an example, assume a semiconductor memory buffer 58 is employed in which $n = 127$; i.e. the frame buffer is capable of storing 128 frames of data. It is further assumed for purposes of the present example that it is desired to have half of the captured frames precede the trigger event and half of the frames follow the trigger event. The head pointer 104 is incremented following the storing of each respective frame. In normal operation, the tail pointer is incremented each time the head pointer is incremented, however, the tail pointer comprises an address which lags the head pointer by sixty four. In the circular buffer frame address 0 follows frame address n (i.e. 127 in the present example).

Upon detection of a trigger event, the tail pointer ceases to increment while frames continue to be stored in subsequent frame locations. A test is performed prior to storing frame data to determine whether the frame location for the data to be stored is one location preceding the tail pointer in which case the frame data pertaining to that frame is stored. No subsequent frames are stored in the frame buffer. Thus, following the trigger event, the buffer contains frame data commencing at a location z and ending at a location $z-1$; i.e. if the tail pointer stopped incrementing upon detection of a trigger event when pointing to address 6, the last captured video image would be stored in location 5 and further image capture and storage would cease.

The sensor 54 may comprise any sensor which provides a trigger output signal in response to a condition which is desired to initiate the capture of the video image or images occurring prior to and following the occurrence of the trigger output signal. For example, the sensor may comprise an accelerometer, an air bag deployment sensor of the type normally used in automobiles to initiate the deployment of an air-bag, a security or fire alarm alert condition sensor used to detect movement, glass breakage, unauthorized entry such as found in a burglar alarm for example fire or smoke, an acoustic signal characteristic of a specific event such as gunshots, or any other signal indicative of a specified event. Moreover, while a single sensor 70 is illustrated for simplicity, it should be appreciated that plural sensors may be employed to activate the capture of video images by the present video recording device and that video image capture may be initiated by any one of such sensors or a combination of such

06906493-080597

sensors.

Upon detection of a trigger event from the sensor 70, the central control processor 54 receives only a predetermined number of additional frames and stores such frames in the semiconductor memory 58 in the successive frame locations within the circular buffer 90. Following the recording of the predetermined number of additional frames, the video recording devices ceases to record further frame data. Thus, if the central controller is programmed to record half the number of frames which are capable of being stored within the semiconductor memory 58 or 58 and 60, as applicable, the video frame data stored within the circular buffer corresponds to an equal number of video frames captured prior to the trigger event and after the trigger event. It is appreciated that any desired percentage of frames may be captured prior to or after the trigger event by specifying how many frames are to be captured and stored after the trigger event.

In one preferred embodiment, it is envisioned that the semiconductor memory will support the storage of 5 frames of video data per second for approximately 30 seconds. Thus, the memory will support the storage of approximately 150 video frames. If it is desired to record the same number of frames before and after detection of a trigger event from sensor 70, seventy five additional frames would be recorded and stored in the circular buffer 90 subsequent to the detection of the trigger event. It should be appreciated that the number of frames that are recorded before and after are a matter of design choice, the only limitation being that the total number of frames to be recorded not exceed the frame capacity of the semiconductor memory. Thus, in the above example in which the video electronics include DRAM supporting storage of 150 video frames, if it was desired to obtain a record which provided ten percent of the frame data prior to the trigger event and ninety percent of the frame data following the trigger event, an additional 135 frames would be recorded and stored subsequent to the trigger event.

Referring again to Fig. 3, the video electronics 42 and sensor 46 are powered by a DC regulator which may derive input power from an AC source, when such is available, from a vehicle battery, or from batteries such as AA cells or any other suitable batteries. When powered by a vehicle battery, it is recognized that in the event of an accident or in some cases, when the vehicle is turned off, the vehicle battery power may cease to provide power. In such event, the battery cells provide an alternative source of power to permit the buffers 58 and 60 to be periodically refreshed (should DRAMs be employed), Since the refresh current is extremely low for DRAMs, the data captured within the buffer may be maintained for many weeks before the captured video data is lost. It is estimated that two or four AA cells will support full

03906493-080597

operation of the video recording device for between two and five hours of recording operation thus permitting fully portable operation of the unit on, for example, a bicycle or in any other application in a steady source of power is not readily available, at a minimal cost in added weight. It is also estimated that two (2) to (4) AA battery cells will maintain the contents within memory for between one (1) and (4) months.

The video recording device is provided with a capture button 72 which serves as a user activatable trigger event. Thus, a user of the device may initiate video capture by pushing the capture button 72. Upon activation of the capture button, a trigger signal is provided to an detected by the central control processor 54. The operation of the video electronics 42 upon user activation of the capture button 72 is otherwise as described with respect to the occurrence of a trigger event in response to a trigger signal provided by the sensor 70.

The still button 74 is optionally provided and coupled to the central control processor 54. Upon activation of the still button, the video electronics captures a video frame and stores the frame within the buffer memory 58 or the extended buffer memory 60. In one embodiment, a frame which is stored as a result of the activation of the still button 74 is stored in a protected memory buffer area which is not employed as a part of the circular buffer 90. In another embodiment of the video recording device, the captured frame is stored within a frame location within the circular buffer, however, the frame is protected from overwriting while video capture within the circular buffer continues. Such may be accomplished via tagging protected frame locations containing captured still frames and checking to determine whether a frame location is protected prior to writing to the frame location. Alternatively, a "still" frame may be stored at the upper, lower or some other designated portion end of the circular buffer and the head and tail pointers controlled so as not to result in the overwriting of the "still" frame.

The purge button 76 is optionally provided and is electronically coupled to the central control processor 54. Upon activation of the purge button, the contents of the circular buffer and any still images that have been captured are erased. Thus, in the event that a user captures images which, for any reason, such user does not desire to retain, they may be erased.

In one embodiment of the invention, the captured digital data is encrypted with any suitable encryption algorithm prior to storing the captured frame data in the buffer memory. The encryption of the captured frame data assures that such data cannot be accessed without authority of the user.

The serial channel 78 is employed to download captured and stored video images to an external Personal Computer (PC),

08906493 080597

Workstation or other suitable device for viewing of the recorded images. Alternatively, the serial channel may be coupled to a radio transmitter to transmit RF signals to a base station for viewing. By way of example, upon detection of gunshots as a trigger event, and storage the specified number of frames within the circular frame buffer, the trigger event is used to cause the transmission of captured video data to a base station over an associated RF transmitter such as found in a police cruiser. The serial channel 78 may comprise a channel compliant with the well known Xmodem protocol, or any other suitable serial channel protocol, for example when the video recording device is employed in a home or another location in which AC power is employed, the serial channel may be appropriately coupled to the AC power line employing the well known X10 protocol for receipt and viewing by a device having an X10 protocol compliant receiver.

An electronic or tamper-evident mechanical seal may be optionally provided to assure that the information contained in the video recording device has not been tampered with prior to viewing to assure the evidentiary integrity of the captured images. The electronic seal may comprise encryption of the video data such that only an individual with authorization may view the recorded data. The mechanical tamper seal may be in the form of a paper or similar seal which is positioned on the case so to as to require rippage of the seal in the event the housing 10, 18 has been opened or if cable connections have been exposed.

The frame rate of video capture may be optionally varied so as to provide a higher frame capture rate or a lower frame capture rate upon the occurrence of a trigger event. The inclusion of an adaptive frame capture rate permits higher or lower frequency rates to be employed in particular applications in which such might be desirable. Additionally, the resolution may be varied so as to provide a different resolution in response to a trigger event. For example, upon recognition of a trigger event, the recording device may record at a higher or lower resolution than that employed prior to the trigger event. Further, an exponential change in resolution may be employed. Finally, the change in resolution may be delayed for a predetermined number of frames following the trigger event.

For example, video data may be stored in the memory buffer using different storage techniques to achieve desired objectives. It may be desired to have higher frame storage rates around the trigger event with successively lower effective storage rates as one progresses further in time away from the trigger event (both before and after the event). It is appreciated that any number of storage methods may be employed via selective addressing of the semiconductor memory to extend the period of time captured within the semiconductor memory buffer, or to achieve almost any frame capture profile that may be desired. Several storage techniques

03906493 080597

illustrated in Figs. 6 through 8 are discussed below.

An automatic gain control (AGC) (not shown) may optionally be electronically coupled between the video image sensor 46 and the A/D converter 50 to compensate for variations in light intensity and to prevent blooming of the captured video image.

The basic method of operation of the video recording device illustrated in the block diagram of Fig. 3 and described above is illustrated in the flow diagram depicted in Fig. 5. As depicted in step 120 in Fig. 5, upon initialization, a counter value *i* is initialized to 0. As illustrated in step 122, the video data corresponding to a video frame is sampled by the A/D converter and converted to digital data. As shown in step 124, the converted frame data is transmitted to the microprocessor. Upon receipt of the frame data, as illustrated in step 126, the microprocessor compresses the frame data so as to permit a greater number of frames to be stored within the circular buffer memory than would otherwise be possible absent such compression. Additionally, as depicted in step 128, the frame data may optionally be encrypted by the microprocessor to prevent unauthorized access to such data. As shown in step 130, the frame data is stored in the next frame location within the circular memory buffer. In the event that any video data has previously been written to the specified memory location within the circular buffer, such data is overwritten. As illustrated in decision step 132, a determination is made whether an event trigger has been received. If no event trigger is received, the counter *i* is reinitialized to 0 and sampling and storage of frame data continues. If the decision step 132 results in a determination that a trigger event has been received, as illustrated in decision step 134, a determination is optionally made whether adaptive rate selection is employed. In the event that adaptive rate selection is employed, the sampling rate of the A/D converter is adjusted as depicted in step 136 and the modified frame rate is employed for subsequent frame storage. In the event that adaptive rate selection is not employed or enabled, following step 132 control passes to step 138 in which the counter *i* is incremented. As shown in decision step 140, a determination is next made as to whether the counter is equal to the specified number of frames to be recorded subsequent to the occurrence of a trigger event. In the event that the determination reveals that the specified number of frames has not been recorded subsequent to the trigger event, control passes to step 122 and sampling continues. In the event the determination of step 140 reveals that the predetermined number of frames have been captured subsequent to the trigger event, control passes to step 142 and further frame capture ceases.

If frames are simply received and stored in successive locations of a circular buffer, it is apparent that the total

03906493 080597

record time will equal the number of frames allocated in the buffer for storage minus one times the frame sampling period. Thus, assuming a semiconductor memory which can hold 150 video frames and a ten (10) frame per second storage rate, the semiconductor memory will only be able to hold 14.9 seconds of video data. If the trigger is adjusted so as to provide for approximately one half of the frames to be recorded prior to the trigger event and one half of the frames subsequent to the trigger event, it is evident that only approximately 7.5 seconds of record time is achieved surrounding the event of interest.

Figs. 6 through 8 illustrate several frame storage techniques which provide for storage of video information over a greater period of time than is achieved by simply storing each successive frame in a successive buffer location as discussed hereinabove wherein the entire buffer pool is treated as a single circular buffer.

The table depicted in Fig. 6 illustrates data samples received successively at .1 second intervals. For simplicity, eight data storage buffers having buffer addresses 0-7 are illustrated although typically many more data buffers would be employed. The data buffers are segregated into two groups of buffers with buffers having addresses 0-3 comprising a first buffer group and buffer having addresses 4-7 comprising a second buffer group. Each group is organized as a circular buffer in which a data sample is stored in the first storage location within the respective group following storage of data sample within the last storage location of the group.

A data sample is stored in the next location within the second group following storage of a predetermined number of data samples within the first group of storage buffers.

In normal operation and in the absence of the occurrence of a trigger event samples are stored as illustrated in Fig. 6. More specifically, the first sample is stored in address 0 of the first group of buffers and the second sample is stored in address 1 of the first group of storage buffers. Following the storage of two data samples in the first group of storage buffers data sample 3 is stored in address 4 which comprises the first address in the second group of storage buffers. The next two data samples comprising samples 4 and 5 are stored in buffer addresses 2 and 3 comprising the next two successive buffer addresses within the first group of storage buffers. Sample 6 is stored in buffer address 5 which comprises the next successive buffer within the second group of storage buffers. This storage technique continues in the absence of a trigger event as illustrated for 17 data samples in Fig. 6.

Once a trigger event has been received, data storage ceases following the storage of a predetermined number of data samples (P_n) within each group (n) of storage buffers where n = the number

03506493-080597

of the respective buffer groups. For example, with reference to Fig. 6, a trigger event is indicated as having occurred following the receipt of data sample 11. Data storage ceases following the storage of two additional data samples in the first group of storage buffers (samples 13 and 14) and two additional samples within the second group of storage buffers (samples 12 and 15). Thus, in the simplified illustration of Fig. 6, the overall storage interval has been expanded from .7 seconds (8 successive samples at .1 second intervals) which would be obtained if all eight buffers were considered as a single buffer group to .9 seconds by organizing the eight buffers as two groups of buffers in which each comprises four buffers. Further, more frames are stored in the vicinity of the trigger event and fewer frames are stored for times farther away in time from the trigger event by employing the presently disclosed technique. It should further be appreciated that by employing greater numbers of groups of buffers, the time interval covered may be substantially increased while still obtaining the highest frame storage resolution immediately before and after the trigger event. Furthermore, it is possible to achieve storage of a greater number or a smaller number of frames before the trigger event or after the trigger event based upon the specification of the number of data samples that are to be stored within respective groups prior to termination of further data sample storage within the respective group.

A further example of the presently disclosed storage technique employing three groups of storage buffers, in which each group comprises four storage buffers, is illustrated in Fig. 7. As illustrated in Fig. 7, a data sample is stored in each successive group only following storage of a predetermined number of data samples within the preceding group. More specifically, the first group of storage buffers comprises buffer addresses 0 to 3, the second group of buffers comprises addresses 4 to 7 and the third group of buffers comprises buffer addresses 8 to 11. The first group of buffers comprise the highest resolution buffers since the greatest number of data samples are stored within this group. Successive groups each store fewer data samples than the preceding group. Any number of variations to the presently disclosed recording technique may be employed to obtain expansion of the time interval covered by the available number of storage buffers while maintaining high resolution recording around the trigger event. For example, while the technique illustrated in Fig. 7 provides for recording sample 9 to the first location of the third storage buffer group following storage of data samples 7 and 8 in address locations 0 and 1 respectively of the first buffer group, sample 7 could instead be stored in address 8 of the third buffer group and samples 8 and 9 could then be stored in address locations 0 and 1 of the first buffer group respectively with the storage pattern

thereafter repeated in a circular manner for each of the respective buffer groups.

Referring again to the illustrated storage technique depicted in Fig. 7, a trigger event 210 is illustrated as occurring between samples 39 and 40. Subsequent to the trigger event 210, recording continues within each buffer group until the predetermined number of data samples for that group has been received and stored. In the example depicted, storage of data samples within each group ceases following receipt and storage of two data samples within each of the respective groups. There is no requirement for the number of data samples to be stored subsequent to the trigger event to be the same for each of the groups and the number of data samples stored after the trigger event may be selected so as to favor storage of information either prior to or subsequent to the trigger event for each of the storage buffer groups.

Assuming a .1 second sampling interval, if a single circular buffer comprising twelve buffer locations were employed without segregating buffers into groups, the interval span would constitute 1.1 seconds. In the example depicted in Fig. 7 the time span covers 2.4 seconds with only three buffer groups although the specific time span varies with the positioning of the trigger event. By increasing the number of buffer groups high resolution may still be obtained around the trigger event with even greater overall time interval coverage.

Another alternative technique for storing video data in the video recording device is illustrated in Fig. 8. A gray code generator, which in the exemplary embodiment comprises a six bit generator, is employed to generate a code in which only a single bit changes from each code to the next. The gray code generator may comprise a gray code counter implemented in hardware or alternatively, a conventional counter may be employed to address a look-up table which contains the respective gray codes and provides such codes as outputs. A buffer pool for storing video data is divided into two parts. One portion of the buffer pool (the Before column) is employed to store video frames received prior to the trigger event 220 and a second portion of the buffer pool is employed to store video data received subsequent to the trigger event. In the example of Fig. 8, six buffers are illustrated in each portion of the buffer pool for purposes of discussion although in practice any number of buffers may be employed within the respective portions and typically the total buffer pool would include many more than 12 buffers to obtain a substantially increased recording time.

Video data is periodically stored on an ongoing basis in the absence of a trigger event, in the buffer address corresponding to the gray code bit which changed when last incremented. Thus, as illustrated, when the gray code changes from 000000 to 000001 video

000000 000001 000010 000011 000100 000101 000110 000111 001000 001001 001010 001011 001100 001101 001110 001111 010000 010001 010010 010011 010100 010101 010110 010111 011000 011001 011010 011011 011100 011101 011110 011111 100000 100001 100010 100011 100100 100101 100110 100111 101000 101001 101010 101011 101100 101101 101110 101111 110000 110001 110010 110011 110100 110101 110110 110111 111000 111001 111010 111011 111100 111101 111110 111111

10

More specifically, following the trigger event 220 video frame 17 is written to buffer 0 of the second buffer pool (outlined highlighted) and video frame 18 is written to buffer 1 within the second buffer pool. Video frame 19, however, is not written to buffer 0 of the second buffer pool after the trigger event, since a video frame (frame 17) has already been written to buffer 0. Video frame 20 is written to buffer 2 (highlighted by outlining) since no prior write has occurred to buffer 2 subsequent to the trigger event 220. Writing or suppression of writing to the second buffer pool continues, as illustrated within the second buffer pool (the After columns) until the gray code is reached corresponding to the gray code immediately preceding the trigger event. In the foregoing manner the video data preceding and subsequent to the trigger event is stored for subsequent retrieval and display.

Thus, following the trigger event, and after termination of recording in the second buffer pool, frames 32, 8, 12, 14, 15 and

16 would be preserved within buffers 5, 3, 2, 1, 0 and 16 respectively of the first portion of the buffer pool and frames 17, 18, 20, 24, 32 and 16 would be preserved in buffers 0, 1, 2, 3, 5 and 4 respectively of the second portion of the buffer pool. The video frame preserved via the present storage technique in the first and second buffer pools in the present illustrative example are highlighted in bold for purposes of identification.

While the above described data storage techniques have been applied to the specific application of video data storage, it is appreciated that these described storage techniques are equally applicable to any application in which it is desired to store data received both before and after a trigger event wherein the timing of the trigger event is indeterminate.

The foregoing video recording device thus provides for the capture and recording of video images occurring both before and after a triggering event in a compact low cost assembly which employs no moving parts such as typically employed in prior art recording devices. It should be understood that modifications to the video recording device and the methods for recording herein described will be apparent to those of ordinary skill in the art without departing from the inventive concepts contained herein. Accordingly, the invention is not to be viewed as limited except by the scope and spirit of the appended claims.

0090493-00297
459080-66490680

CLAIMS

What is claimed is:

1. A video recording device for capturing video frame data in response to a trigger event, said recording device comprising:
 - at least one image sensor operative to produce an output frame data signal representative of video images impinging said at least one sensor;
 - a central control processor having inputs for receiving video frame data and an input for receiving a trigger signal;
 - a converter coupled between said image sensor and said central control processor and operative to convert said output frame data signal a video frame data signal and to communicate said video frame data signal to said central control processor;
 - a semiconductor memory employed as a circular buffer memory, said semiconductor memory in electrical communication with said central control processor, said semiconductor memory having a plurality of locations for storing a corresponding plurality of frames comprising frame data corresponding to portions of said video frame data signal;
 - said central control processor being operative to store respective frames in successive ones of said locations of said circular buffer memory in the absence of said trigger signal and to store respective frames only in a predetermined number of successive locations of said circular buffer memory following receipt of said trigger signal.
2. The video recording device of claim 1 wherein said device further includes a sensor operative to produce said trigger signal.
3. The video recording device of claim 2 wherein said sensor comprises an accelerometer.
4. The video recording device of claim 1 wherein said device further includes a capture switch and said device is operative to store only a predetermined number of frames within said semiconductor memory following user activation of said capture switch.
5. The video recording device of claim 1 wherein said device is further operative to store data representative of a single video frame within said semiconductor memory upon user activation of a switch.
6. The video recording device of claim 1 wherein said central control processor is further operative to compress video frame data prior to the storage of respective frames within said

08906493 080597

semiconductor memory.

7. The video recording device of claim 1 wherein said central control processor is capable of storing frames in said semiconductor memory at a first frame rate and a second frame rate, said processor being operative to store frames in said semiconductor memory at said first frame rate prior to said trigger event and being operative to store said frames in said semiconductor memory at said second frame rate subsequent to said trigger event.

8. The video recording device of claim 7 wherein said second frame rate is greater than said first frame rate.

9. The video recording device of claim 7 wherein said central control processor is operative to store frame data only in approximately one-half the number of said plurality of frame locations contained in said semiconductor memory following receipt of said trigger signal.

10. The video recording device of claim 1 wherein said video recording device includes plural image sensors coupled to said central control processor through said converter and each sensor is operative to produce a respective output frame data signal representative of video images impinging the respective sensor, wherein said semiconductor memory is structured as a plurality of circular buffer memories corresponding in number to said plurality of image sensors and wherein said central control processor is operative to continue to store frames representative of the respective video images impinging respective ones of said image sensors in successive ones of said frame locations of said plurality of circular buffer memories in the absence of said trigger signal and to store said frames only in a predetermined number of successive locations of said circular buffer memories following receipt of said trigger signal.

11. The video recording device of claim 1 wherein said image sensor comprises a charge coupled device.

12. The video recording device of claim 11 wherein said device further comprises a lens selectively positioned so as to focus a video image on said image sensor and cover a predetermined viewing angle.

13. The video recording device of claim 1 wherein said image sensor comprises an artificial retina.

08906493 080597

14. The video recording device of claim 13 wherein said device further comprises a lens selectively positioned so as to focus a video image on said artificial retina and cover a predetermined viewing angle.

15. A method for recording video frames in response to a trigger signal comprising the steps of:

receiving at an image sensor, video frame images and producing an image sensor output signal representative of said received video frame images;

converting said image sensor output signal to digital video signals, wherein a predetermined number of said video signals comprise a frame;

continuing to store data corresponding to successive frames in a semiconductor buffer memory in the absence of the detection of said trigger signal by a central control processor; and

storing a plurality of frames in said semiconductor buffer memory subsequent to the detection of said trigger signal by said central control processor.

16. The method of claim 15 further comprising the step of compressing said digital video signals prior to storing said frames in said semiconductor buffer memory.

17. The method of claim 16 wherein said compressing step comprises the step of compressing said digital video signals with an asymmetric compression routine prior to storing said frames in said semiconductor buffer memory.

18. The method of claim 16 further comprising the step of encrypting said digital video signals prior to storing said frames in said semiconductor buffer memory.

19. The method of claim 15 further comprising the steps of:

storing said frames in said semiconductor buffer memory at a first frame rate prior to detection of said trigger event; and

storing said frames in said semiconductor buffer memory at a second frame rate subsequent to the detection of said trigger event.

20. The method of claim 19 wherein said second storing step comprises the step of storing said frames in said semiconductor buffer memory at said second frame rate subsequent to the detection of said trigger event, wherein said second frame rate is greater than said first frame rate.

03906493-080597

21. The method of claim 19 wherein said second storing step comprises the step of storing said frames in said semiconductor buffer memory at said second frame rate subsequent to the detection of said trigger event, wherein said second frame rate is less than said first frame rate.

22. A method for storing data in a storage device having a plurality of storage buffers comprising the steps of:
 successively receiving a plurality of data samples;
 segregating said storage buffers into a plurality of groups (1 through n) of storage buffers, wherein each of said groups includes at least one buffer; and
 storing a smaller number of data samples in each successive group of storage buffers per unit interval of time.

23. The method of claim 22 wherein said segregating step comprises the step of segregating said storage buffers into a plurality of groups (1 through n) of storage buffers and wherein each group is organized as a group of circular storage buffers and wherein said storing step comprises the step of storing selected ones said successively received data samples in successive storage locations within each of said groups of storage buffers.

24. The method of claim 23 wherein said storing step comprises the step of storing one of said received data samples in a selected one of said groups following the storage of a predetermined number of data samples in the preceding group.

25. The method of claim 24 wherein said storing step comprises the step of storing one of said received data samples in a selected one of said groups following the storage of a first predetermined number of data samples in the preceding group and storage of a second predetermined number of data samples in the first group (group 1) of said storage buffers.

26. The method of claim 25 wherein said storing step comprises the step of storing one of said received data samples in a selected one of said groups following the storage of two (2) data samples in the preceding group and storage of two (2) data samples in the first group (group 1) of said storage buffers.

27. The method of claim 22 further comprising the step of ceasing to store data samples in each respective group upon storage of a predetermined number (P_n) of data samples within the respective group, where n corresponds to the number of the respective group.

06906493-060597
455080" E6490680

28. The method of claim 27 wherein said successively receiving step comprises the step of successively receiving a plurality of data samples wherein each of said data samples corresponds to a video frame.

29. A method for storing data in a storage device having a plurality of storage buffers comprising the steps of:

successively receiving a plurality of data samples;
segregating said storage buffers into first and second buffer pool portions having n buffers n in each portion, wherein each buffer pool portion includes at least two buffer;
generating successive gray codes having a plurality of bit locations with a gray code generator, wherein only one of said bit locations changes in successive codes;
storing successively received data samples in a selected one of buffers in the first buffer pool portion specified by a buffer location address associated with the changed gray code bit location prior to receipt of a trigger event.

30. The method of claim 29 further comprising the steps of storing successively received data samples in a selected one of buffers in the second buffer pool portion specified by a buffer location address associated with the changed gray code bit location after receipt of said trigger event; and

suppressing writes to each buffer location within said second buffer pool which has been previously written to subsequent to said trigger event.

31. The method of claim 30 further comprising the steps:

cycling through said gray codes once subsequent to said trigger event; and
terminating writing to said second buffer pool following said cycling step.

03906493-080597

ABSTRACT

A compact video image recording device for recording video images before and after a triggering event and which utilizes no moving parts is disclosed. The recording device includes at least one camera wherein each camera comprises a lens and a video image sensor. Each video image sensor generates an electronic signal representative of a video image impinging the respective sensor. The output of each image sensor is processed, compressed and generally employed to produce frame data which are successively stored in a successive frame locations of a semiconductor memory organized as a circular buffer memory. Upon the occurrence of a triggering event, a additional frames are stored in the buffer memory and further storage of frames then terminates. A video record is thus created of video images received both before and after the triggering event via a device which contains no moving parts and which can withstand substantial shock and vibration.

105002.wp

00506493-08097
255080-6490680




Fig. 1

08905493, 080597




Fig. 2a




Fig. 2b







Fig. 3

**Fig. 4a****Fig. 4b**

**Fig. 5**




Fig. 6





Fig. 7

		Gray Code						Before						After					
		5	4	3	2	1	0	5	4	3	2	1	0	5	4	3	2	1	0
1	FRAME	0	0	0	0	0	0						1						
2		0	0	0	0	0	1					2							
3		0	0	0	0	0	1						3						
4		0	0	0	1	1	0				4								
5		0	0	0	1	1	1						5						
6		0	0	0	1	0	1					6							
7		0	0	0	1	0	0						7						
8		0	0	1	1	0	0			8									
9		0	0	1	1	0	1						9						
10		0	0	1	1	1	1					10							
11		0	0	1	1	1	0						11						
12		0	0	1	0	1	0			12									
13		0	0	1	0	1	1						13						
14		0	0	1	0	0	1					14							
15		0	0	1	0	0	0						15						
16		0	1	1	0	0	0		16					16					
17		0	1	1	0	0	1						17						
18		0	1	1	0	1	1					18							
19		0	1	1	0	1	0						19						
20		0	1	1	1	1	0			20						20			
21		0	1	1	1	1	1						21						
22		0	1	1	1	0	1					22							
23		0	1	1	1	0	0						23						
24		0	1	0	1	0	0			24					24				
25		0	1	0	1	0	1						25						
26		0	1	0	1	1	1					26							
27		0	1	0	1	1	0						27						
28		1	1	0	0	1	0				28								
29		0	1	0	0	1	1						29						
30		0	1	0	0	0	1					30							
31		0	1	0	0	0	0						31						
32		1	1	0	0	0	0		32					32					

Fig. 8

DECLARATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

VIDEO RECORDING DEVICE RESPONSIVE TO TRIGGERING EVENT

the specification of which (check one):

☒ is attached hereto. ☐ was filed _____ as Application No. _____;
amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations §1.56(a).

I hereby claim foreign priority benefits under Title 35, USC §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Prior Foreign Application(s)</u>		<u>Date Filed</u>	<u>Priority Claimed</u>	
(Number) _____	(Country) _____	(Day/Month/Year) _____	<input type="checkbox"/> Yes	<input type="checkbox"/> No
(Number) _____	(Country) _____	(Day/Month/Year) _____	<input type="checkbox"/> Yes	<input type="checkbox"/> No
(Number) _____	(Country) _____	(Day/Month/Year) _____	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, USC §119(e) of any United States provisional application(s) listed below:

(Application Number) _____	(Filing Date) _____
(Application Number) _____	(Filing Date) _____
(Application Number) _____	(Filing Date) _____
(Application Number) _____	(Filing Date) _____

Attorney
Docket No.: MERL-1163

I hereby claim the benefit under Title 35 USC §120 of any United States application(s) listed below and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 USC §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application No.)	(Filing Date)	(Patented/pending/abandoned)
(Application No.)	(Filing Date)	(Patented/pending/abandoned)
(Application No.)	(Filing Date)	(Patented/pending/abandoned)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) to prosecute this application and transact all business connected therewith in the Patent and Trademark Office, and to file with the USRO any International Application based thereon.

Robert K. Tendler, Reg. No. 24,581

and

Stanley M. Schurgin, Reg. No. 20,979
Charles L. Gagnebin III, Reg. No. 25,467
Paul J. Hayes, Reg. No. 28,307

Victor B. Lebovici, Reg. No. 30,864
Eugene A. Feher, Reg. No. 33,171
Beverly E. Hjorth, Reg. No. 32,033

Address all correspondence to:

ROBERT K. TENDLER
65 ATLANTIC AVENUE
BOSTON, MASSACHUSETTS 02110
(617) 723-7268

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor:		
William T. Freeman		
City of Residence	State or Country	Country of Citizenship
Acton	Massachusetts	U.S.
Post Office Address	City	State or Country Zip Code
16 Half Moon Hill	Acton	Massachusetts 01720
Signature: (Please sign and date in permanent ink.)		Date signed:
X <i>William T. Freeman</i>		X Aug 5, 1997

Attorney
Docket No.: MERL-1163

Full Name of Second Joint Inventor:		
William S. Yerazunis		
City of Residence	State or Country	Country of Citizenship
Acton	Massachusetts	U.S.
Post Office Address	City	State or Country Zip Code
24 Nash Road	Acton	Massachusetts 01720
Signature: (Please sign and date in permanent ink.) X <i>William S. Yerazunis</i>		Date signed: X August 5, 1997

Full Name of Third Joint Inventor:		
Walter A. Hiatt		
City of Residence	State or Country	Country of Citizenship
Waltham	Massachusetts	U.S.
Post Office Address	City	State or Country Zip Code
310 College Farm Road, Apt. 3	Waltham	Massachusetts 02154
Signature: (Please sign and date in permanent ink.) X		Date signed: X